





ALUMINIUM ALLOY AERIAL LIFT PLATFORM



Standard Equipment

- Leveling outrigger device
- Two controllers operation
- Emergency stop button
- Emergency lowering system
- Overloading limited
- Battery charge indicator
- Limit switch



TECHNICAL DATA			GTWY601	GTWY801	GTWY1001
Capacity		kg	150	125	125
Max Platform height	H1	m	6	8	10
Max working height	H2	m	8	10	12
Platform size		m	0.63x0.64	0.63x0.64	0.63x0.64
Overall length	A	m	1.42	1.42	1.42
Overall width	B	m	0.82	0.82	0.82
Overall height	H3	m	1.92	2.00	1.90
Outrigger Footprint	L/W		1.90x1.75	1.90x1.75	1.90x1.75
Ground clearance		m	0.06	0.06	0.06
Wheelbase			1.11	1.11	1.11
Front wheels size		inch	5	5	5
Rear wheel		inch	8	8	8
Battery			2-12V/65Ah	2-12V/65Ah	2-12V/65Ah
Integrated charger			12V/15A	12V/15A	12V/15A
Lifting motor	AC		110-230V/0.75kw	110-230V/0.75kw	110-230V/0.75kw
Lifting motor	DC		12V/0.75kw	12V/0.75kw	12V/0.75kw
Lifting time	S		38	44	46
Lowering time	S		35	38	40
Self weight		kg	415 (AC) , 450 (DC)	450 (AC) , 485 (DC)	490 (AC) , 525 (DC)

Specifications are subject to change without notice.



Under the Management of Estel Company Limited

79/5 Moo 2 Mahasawat Bangkray Nonthaburi 11130 Thailand. Tel. 0-2985-2081-9 Ext. 224

Fax. 0-2985-2313 Website : <http://www.rhino-estel.com> E-mail : rhino.estel@gmail.com