





# ALUMINIUM ALLOY AERIAL LIFT PLATFORM



## Standard Equipment

- Leveling outrigger device
- Two controllers operation
- Emergency stop button
- Emergency lowering system
- Overloading limited
- Battery charge indicator
- Limit switch



TECHNICAL DATA			GTWY802	GTWY1002	GTWY1202
Capacity		kg	300	250	200
Max Platform height	H1	m	8	10	12
Max working height	H2	m	10	12	14
Platform size		m	1.28x0.66	1.54x0.66	1.54x0.66
Overall length	A	m	1.53	1.79	1.79
Overall width	B	m	0.82	0.82	0.87
Overall height	H3	m	1.81	1.86	2.03
Outrigger Footprint	L/W		1.65x1.66	2.13x1.89	2.13x1.94
Ground clearance		m	0.08	0.08	0.08
Wheelbase			1.18	1.44	1.44
Front wheels size		inch	8	8	8
Rear wheel		inch	8	8	8
Battery			2-12V/65Ah	2-12V/65Ah	2-12V/65Ah
Integrated charger			12V/15A	12V/15A	12V/15A
Lifting motor	AC		110-230V/1.5kw	110-230V/1.5kw	110-230V/1.5kw
Lifting motor	DC		12V/1.5kw	12V/1.5kw	12V/1.5kw
Lifting time	S		62	70	75
Lowering time	S		43	46	54
Self weight		kg	630 (AC), 670 (DC)	730 (AC), 770 (DC)	825 (AC), 865 (DC)

Specifications are subject to change without notice.



Under the Management of Estel Company Limited

79/5 Moo 2 Mahasawat Bangkruey Nonthaburi 11130 Thailand. Tel. 0-2985-2081-9 Ext. 224

Fax. 0-2985-2313 Website : <http://www.rhino-estel.com> E-mail : rhino.estel@gmail.com